

## Rol-A-Lifts | 1 - 6 Ton | M Series



Model M-12

- Top clamps to secure narrow or heavy loads.
- Side belts to stabilize load and prevent slippage during movement.
- Under the load belt secures load.
- Polyurethane casters in single or dual wheel for floor protection and weight distribution.
- 4 position swivel locks are available on all casters.

### Specifications

Model	Cap. Per Pair (lbs.)	Max. Hydraulic Lift (in.)	Standard Wheels	Wheel Size (in.)	Overall Ht. (in.)	Overall Width (in.)	Caster Centers (in.)	Overall Depth (in.)	Forks Adjustable (in.)	Fork Length (in.)	Fork Thickness (in.)	Weight (lbs.)
M-2	2,000	4 1/3	Phenolic	5 x 2	47 1/2	22	18	12 1/2	7 1/4 - 17 1/2	5	3/4	160
M-4	4,000	12 13/16"	Phenolic	6 x 2	44	23		16 1/2	5 - 19 1/2		1 1/8	325
M-4-6	4,000-6,000	12 2/16" / 6"	Phenolic	6 x 2	44	23		16 3/4	6 - 19 1/2		1 1/8	340
M-6	6,000	4 3/4	Phenolic	6 x 2	42 1/2	23		16 3/4	6 - 19 1/2		1 1/8	335
M-8	8,000	4 3/4	Semi-Steel	8 x 2 1/2	45	23 1/8		17 1/4	7 1/4 - 19 1/2		1 1/8	400
M-10	10,000	4 3/4	Semi-Steel	8 x 3	46	24		18	9 1/4 - 19 1/2		1 1/8	438
M-12	12,000	4 3/4	Forged-Steel	8 x 2 1/2	46	24		18	9 1/4 - 19 1/2		1 1/8	470

*Green shading reflects rental inventory.*