

## Hydraulic Gantries | 20 – 40 Ton | MiniJack | 2 or 4 Point Hydraulic Gantries



### MiniJack™ Specifications

#### Standard Equipment:

**Lifting Units (Each):** Maximum Extended Height: 16' 1/8" (4,877 mm).

Retracted Height: 6' 1/8" (1,829 mm). 10 (9) ton capacity. Light weight platform with cylinder support struts. Steel wheels with anti-friction bearings. Self-contained integral hydraulic system with preparation for the addition of a remote control system, required to operate the lifting units. Header plate on lift cylinder for attaching lift beam. Maneuvering dolly to ease placement of each pair of lifting units. Standard paint color is Lift Systems' yellow.

\*A.S.W.: 1,800 lbs. (817kg)

**Integral Hydraulic Power System:** 14 gal. (53L) reservoir. Necessary filters. Gear pump at 1 g.p.m. (3.8 l.p.m.). Standard power is electric 115 volt (15.2 full load amps), domestic 1.5 HP (1.11 kw) @ 60 Hz power and international 1 HP (0.74 kw) @ 50 Hz.

#### Optional Equipment:

**Hydraulic Power Drive:** High traction rubber drive wheels with hydraulic motor drive. Attaches to end of lift unit for smooth continuous travel.

\*A.S.W. per pair: 120 lbs. (54 kg)

**Lifting Links (Each):** 10 (9) ton capacity. One link per lifting unit. Consult factory for custom links to suit customer needs and applications.

\*A.S.W.: 38 lbs. (17.24 kg)

**Runway Track:** See page 88.

Specifications							
Model	Capacity (Tons)	Max. Height	Max Operating PSI	Length (in)	Width (in)	Height Retracted	Weight
2020SC 2 Point	20 to 16' 1/8"	16' 1/8"	1800 (124 bar)	51	28	6' 1/8"	1850
4040SC 4 Point	40 to 16' 1/8"	16' 1/8"	1800 (124 bar)	51	28	6' 1/8"	1850

*Green shading reflects rental inventory.*

## Hydraulic Gantries | 20 – 40 Ton | MiniJack | 2 or 4 Point Hydraulic Gantries

