

## Hydraulic Jacks | 5 - 60 Ton | PS Series | Hydraulic Toe Jacks



Specifications										
Model	Capacity (Tons)	Claw Capacity (Tons)	Stroke (in)	Lift Per Stroke (in.)	Weight of Jack (lbs.)	Weight of Claw (lbs.)	Working Pressure (PSI)	Effort on Lever (max) (lbs.)	Oil Capacity (pints)	Service Kit Number
9501W	5	5	7	.21	40	8	-	99	-	995125
PS630C	30	12	6	.026	34	11	9,350	115	1.5	133511
PS1230C	30	12	12	.026	52	17	9,350	115	3	133511
PS660C	60	24	6	.013	61	34.5	9,350	115	3	133518
PS1260C	60	24	12	.013	97	47	9,350	115	5	133518

*Green shading reflects rental inventory.*

Dimensions									
Model	A Width (in.)	B Center Ram to Claw (in.)	C Base Length (in.)	D Overall Depth (in.)	F Ram Diameter (in.)	H Closed Height (in.)	J Base to Claw (in.)	K Claw Depth (in.)	
9501W	4.5	3.17	8.66	10.35	2.24	12.8	1.61	2.05	
PS630C	5.5	5.265	10.75	9.25	3	11.062	2.875	1.77	
PS1230C	5.5	5.625	10.75	12.25	3	18.5	2.875	1.77	
PS660C	7.5	7.125	13.375	11.25	4.25	12.875	2.875	1.89	
PS1260C	7.5	7.125	13.375	15.125	4.25	21	2.875	1.89	

*Green shading reflects rental inventory.*